

NPAR TESTS
 /K-S (NORMAL) =RES_1
 /MISSING ANALYSIS.

NPar Tests

Notes		
Output Created		22-May-2023 19:12:50
Comments		
Input	Active Dataset	DataSet0
	Filter	<none>
	Weight	<none>
	Split File	<none>
	N of Rows in Working Data	23
	File	
Missing Value Handling	Definition of Missing	User-defined missing values are treated as missing.
	Cases Used	Statistics for each test are based on all cases with valid data for the variable(s) used in that test.
Syntax		NPAR TESTS /K-S(NORMAL)=RES_1 /MISSING ANALYSIS.
Resources	Processor Time	00 00:00:00.016
	Elapsed Time	00 00:00:00.046
	Number of Cases Allowed ^a	196608

a. Based on availability of workspace memory.

[DataSet0]

One-Sample Kolmogorov-Smirnov Test

		Unstandardized Residual
N		23
Normal Parameters ^{a,b}	Mean	.0000000
	Std. Deviation	5.35981960
Most Extreme Differences	Absolute	.133
	Positive	.088
	Negative	-.133
Kolmogorov-Smirnov Z		.639
Asymp. Sig. (2-tailed)		.808

a. Test distribution is Normal.

b. Calculated from data

